

US006732579B2

## (12) United States Patent Keith et al.

(54) TURBULENT BOUNDARY LAYER

US 2004/0065146 A1 Apr. 8, 2004

(56)

(10) Patent No.: US 6,732,579 B2 (45) Date of Patent: May 11, 2004

	THICKNESS ESTIMATION METHOD AND APPARATUS				
(75)	Inventors:	William L. Keith, Ashaway, RI (US); Kimberly M. Cipolla, Portsmouth, RI (US)			
(73)	Assignce:	The United States of America as represented by the Secretary of the Navy, Washington, DC (US)			
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.			
(21)	Appl. No.: 10/267,099				
(22)	Filed:	Oct. 8, 2002			
(65)		Prior Publication Data			

Int. Cl.<sup>7</sup> ...... G01M 9/00

U.S. Cl. 73/147

References Cited

U.S. PATENT DOCUMENTS

4,896,098 A	•	1/1990	Haritonidis et al.	324/663
5,199,298 A	*	4/1993	Ng et al	73/54.01
5,341,677 A	٠	8/1994	Maris	73/147
5,511,428 A	•	4/1996	Goldberg et al.	<i>73/777</i>

<sup>\*</sup> cited by examiner

Primary Examiner—Edward Lefkowitz

Assistant Examiner—Jermaine Jenkins
(74) Attorney, Agent, or Firm—James M. Kasischke;

Michael F. Oglo; Jean-Paul A. Nasser

## (57) ABSTRACT

A method and apparatus are presented for determining turbulent boundary layer thickness. In this method and apparatus, a pair of sensors are mounted to a solid surface interfacing with a fluid at two separate stream wise locations. A voltage output from the pair of sensors is recorded and a real non-dimensional value of a correlation coefficient is computed with measured data from the recorded voltage. A laboratory non-dimensional value of the correlation coefficient is independently determined from laboratory data. The real non-dimensional value is compared with the laboratory non-dimensional value to obtain a boundary layer thickness having a value which minimizes a difference between the values of the real non-dimensional value and the laboratory non-dimensional value.

## 12 Claims, 2 Drawing Sheets

